

### ST1 - Rãnh Bằng Tee (*bán kính ngắn*)

- ◆ NPS2" (DN50) đến NPS8" (DN200)
- ◆ Vật liệu: ASTM A536 Gr. 65-45-12
- ◆ Kích thước rãnh cắt theo tiêu chuẩn: ANSI/AWWA C606
- ◆ Bề mặt hoàn thiện: Sơn epoxy màu đỏ RAL3000, có thể lựa chọn mạ kẽm nhúng nóng hoặc sơn màu cam.



#### Kích Thước

Kích thước định danh DN / NPS	Đường kính ngoài ống mm / in	Áp suất tối đa MPa / psi	CE mm / in	Khối lượng kg / lbs
50 2"	60.3 2.375	2.07 300	70 2.76	0.85 1.87
65 2½"	73.0 2.875	2.07 300	76 2.99	1.3 2.87
65 3" O.D	76.1 3.000	2.07 300	76 2.99	1.3 2.87
80 3"	88.9 3.500	2.07 300	86 3.39	1.6 3.53
100 4"	114.3 4.500	2.07 300	102 4.02	2.6 5.73
125 5½" O.D	139.7 5.500	2.07 300	124 4.88	4.0 8.82
125 5"	141.3 5.563	2.07 300	124 4.88	4.0 8.82
150 6½" O.D	165.1 6.500	2.07 300	140 5.51	6.6 14.55
150 6"	168.3 6.625	2.07 300	140 5.51	6.7 14.77
200 8"	219.1 8.625	2.07 300	173 6.81	12.9 28.44



Bề mặt hoàn thiện:



Sơn màu cam

